

# Šroubení a tvarovky

z nerezové oceli

NEREZ

1

## Návarky dle DIN 2982 s vnějším kuželovým závitem

	Obj. č.	Závit 1	Průměr	Délka	Tlak (bar)	Materiál
•	AX019-1810	R 1/8"	10,2 mm	30	16	nerez 1.4571
•	AX019-1413	R 1/4"	13,5 mm	30	16	nerez 1.4571
•	AX019-3817	R 3/8"	17,2 mm	30	16	nerez 1.4571
•	AX019-1221	R 1/2"	21,3 mm	35	16	nerez 1.4571
•	AX019-3427	R 3/4"	26,9 mm	40	16	nerez 1.4571
•	AX019-1034	R 1"	33,7 mm	40	16	nerez 1.4571



## Mufny s vnitřními trubkovými závitmi

	Obj. č.	Závit 1	Závit 2	SW	Tlak (bar)	Materiál
•	AX007-1818	G 1/8"	G 1/8"	14	40	nerez 1.4571
•	AX007-1814	G 1/8"	G 1/4"	17	40	nerez 1.4571
•	AX007-1414	G 1/4"	G 1/4"	17	40	nerez 1.4571
•	AX007-1438	G 1/4"	G 3/8"	22	40	nerez 1.4571
•	AX007-3838	G 3/8"	G 3/8"	22	40	nerez 1.4571
•	AX007-3812	G 3/8"	G 1/2"	27	40	nerez 1.4571
•	AX007-1212	G 1/2"	G 1/2"	27	40	nerez 1.4571
•	AX007-1234	G 1/2"	G 3/4"	32	40	nerez 1.4571
•	AX007-3434	G 3/4"	G 3/4"	32	40	nerez 1.4571
•	AX007-3410	G 3/4"	G 1"	41	40	nerez 1.4571
•	AX007-1010	G 1"	G 1"	41	40	nerez 1.4571



## Záslepky se šestihranem a s vnějším závitem

	Obj. č.	Závit	SW	Tlak (bar)	Materiál
•	AX008-18	G 1/8"	14	40	nerez 1.4571
•	AX008-14	G 1/4"	17	40	nerez 1.4571
•	AX008-38	G 3/8"	19	40	nerez 1.4571
•	AX008-12	G 1/2"	24	40	nerez 1.4571
•	AX008-34	G 3/4"	---	40	nerez 1.4571
•	AX008-10	G 1"	---	40	nerez 1.4571



## Záslepky s imbusem a osazením, s vnějším závitem

	Obj. č.	Závit	Tlak (bar)	Materiál
•	AX009-18	G 1/8"	40	nerez 1.4571
•	AX009-14	G 1/4"	40	nerez 1.4571
•	AX009-38	G 3/8"	40	nerez 1.4571
•	AX009-12	G 1/2"	40	nerez 1.4571
•	AX009-34	G 3/4"	40	nerez 1.4571
•	AX009-10	G 1"	40	nerez 1.4571



## Záslepky s imbusem bez osazení, s vnějším závitem

	Obj. č.	Závit	Tlak (bar)	Materiál
•	AX012-18	R 1/8"	40	nerez 1.4571
•	AX012-14	R 1/4"	40	nerez 1.4571
•	AX012-38	R 3/8"	40	nerez 1.4571
•	AX012-12	R 1/2"	40	nerez 1.4571
•	AX012-34	R 3/4"	40	nerez 1.4571
•	AX012-10	R 1"	40	nerez 1.4571

