

## Úchyty pneumatických válců

pro válce ISO 15 552, z hliníku

Zadní oka – typ ASV.. ALIS						
	Obj. č.	Kód	Pro válec	Rozteč	Průměr čepu	Otvory pro šrouby
●	042081	ASV32ALIS	∅ 32 mm	26	10	6,6
●	042082	ASV40ALIS	∅ 40 mm	28	12	6,6
●	042083	ASV50ALIS	∅ 50 mm	32	12	9
●	042084	ASV63ALIS	∅ 63 mm	40	16	9
●	042085	ASV80ALIS	∅ 80 mm	50	16	11
●	042086	ASV100ALIS	∅ 100 mm	60	20	11
○	042087	ASV125ALIS	∅ 125 mm	70	25	14
○	040395	ASV160ALIS	∅ 160 mm	90	30	14
○	040396	ASV200ALIS	∅ 200 mm	90	30	18

Rozsah dodávky: průměry 32-125 mm úchyt a sada 4 šroubů; od průměru 160 mm pouze úchyt bez šroubů, lze spojit se zadní vidlicí CF.



Zadní oka 90° – typ AS.. ALIS						
	Obj. č.	Kód	Pro válec	Rozteč	Průměr čepu	Otvory pro šrouby
○	040361	AS32ALIS	∅ 32 mm	26	10	7
○	040362	AS40ALIS	∅ 40 mm	28	12	9
○	040363	AS50ALIS	∅ 50 mm	32	12	9
○	040364	AS63ALIS	∅ 63 mm	40	16	11
○	040365	AS80ALIS	∅ 80 mm	50	16	11
○	040366	AS100ALIS	∅ 100 mm	60	20	14
○	040367	AS125ALIS	∅ 125 mm	70	25	14
○	040368	AS160ALIS	∅ 160 mm	90	30	18
○	040369	AS200ALIS	∅ 200 mm	90	30	18

Lze spojit se zadní vidlicí CF.



Zadní výkyvná oka – typ CMS.. ALIS						
	Obj. č.	Kód	Pro válec	Rozteč	Průměr čepu	Otvory pro šrouby
○	040151	CMS32ALIS	∅ 32 mm	14	10	6,6
○	040152	CMS40ALIS	∅ 40 mm	16	12	6,6
○	040153	CMS50ALIS	∅ 50 mm	21	16	9
○	040154	CMS63ALIS	∅ 63 mm	21	16	9
○	040155	CMS80ALIS	∅ 80 mm	25	20	11
○	040156	CMS100ALIS	∅ 100 mm	25	20	11
○	040157	CMS125ALIS	∅ 125 mm	37	30	13,5
○	040158	CMS160ALIS	∅ 160 mm	43	35	18
○	040159	CMS200ALIS	∅ 200 mm	43	35	18

Lze spojit se zadní vidlicí CF.



Vysoké patky – typ P.. ALIS						
	Obj. č.	Kód	Pro válec	Průměr otvoru	Výška patky	Otvory pro šrouby
○	040141	P32ALIS	∅ 32 mm	30	55	7
○	040142	P40ALIS	∅ 40 mm	35	62	9
○	040143	P50ALIS	∅ 50 mm	40	78	9
○	040144	P63ALIS	∅ 63 mm	45	88	9
○	040145	P80ALIS	∅ 80 mm	45	111	12
○	040146	P100ALIS	∅ 100 mm	56	128	14
○	040147	P125ALIS	∅ 125 mm	60	161	16
○	040148	P160ALIS	∅ 160 mm	65	205	18
○	040149	P200ALIS	∅ 200 mm	75	245	22

