











PREMIUM™ STEAM MASTER



							
mm	mm	mm	Bar	Bar	Kg/m	m	REF.
13	25	6	18	180	0.5	40	3605-12001
16	30	7	18	180	0.7	40	3605-12002
19	33	7	18	180	0.8	40	3605-12003
25	40	7.5	18	180	1.1	40	3605-12004
32	48	8	18	180	1.5	40	3605-12005
38	54	8	18	180	1.8	40	3605-12006
51	67	8	18	180	2.3	40	3605-12007

RECOMMENDED FOR

Premium steam hose for the transport of pressurized saturated steam at 210°C up to a max. 18 bar working pressure or pressurized hot water.

TUBE

Black EPDM, smooth, conductive

REINFORCEMENT

Two high tensile steel braids

COVER

EPDM rubber, smooth, black, all sizes are pinpricked. Extremely weather resistance cover

TEMPERATURE

up to +210°C

BURST PRESSURE

180 bar

ELECTRICALLY CONDUCTIVE

R < 10⁶ Ohm

STANDARDS

EN ISO 6134:2005-2A

BRANDING TRANSFER LABEL

PREMIUM™ STEAM MASTER - EN ISO 6134:2005-2A STEAM 18 BAR 210°C Ω - DRAIN AFTER USE

BRANDING EMBOSSED LABEL

GATES PREMIUM™ STEAM MASTER - EN ISO 6134:2005-2A STEAM 18 BAR - DIAM mm - Ω - Q - year



**KOMPRESORY
VZDUCHOTECHNIKA** s.r.o.
Vše pro stlačený vzduch na jednom místě

E: info@kompresory-vzduchotechnika.cz

E: objednavky@kompresory-vzduchotechnika.cz

T: +420 311 532 091, **M:** +420 773 489 530, **M:** +420 603 432 326