



TU 25

Multi-Purpose Mineral Oil Hose



Application:

- ① Flexible delivery hose suitable for industrial oils, unleaded fuels (EN228:2004), diesel (EN 590:2004) heating oils (DIN 51 603 parts 1 - 5) also for compressed air.
- ① Applications in industry, garages, filling stations and automobile repair shops.

Notice:

- ① Electrically conductive: Resistance $R < 10^6 \text{ Ohm/m}$ (according to EN ISO 8031:1997).
- ① ATTENTION: Not to be used as a petrol pump hose.



Temperature range: -40°C / +80°C.

Safety factor: 3.15 : 1

Tube: NBR, black, smooth, electrically conductive.

Reinforcement: Textile spiral construction.

Cover: NBR/SBR, black, smooth, abrasion resistant, oil and weather resistant.

Marking: Continuous coloured marking, white: "SEMPERIT S TU 25 Öl/Luft Oil/Air PN 25 bar Conductive $R < 10^6 \text{ Ohm/m}$ ". Additionally: 3 red longitudinal stripes.

Article number	Internal-Ø in		Wall width in mm	External-Ø in mm	Work. pressure (max.) bar	Number of inserts	Bending radius (min.) in mm	Weight approx. kg/m	Coil length (max.) m
	mm	inches							
68175 0649	6,0	1/4	4,0	14,0	25	2	40	0,17	100
68175 0849	8,0	5/16	4,0	16,0	25	2	50	0,19	100
68175 1040	10,0	3/8	4,0	18,0	25	2	60	0,23	50
68175 1340	13,0	1/2	4,0	21,0	25	2	80	0,28	50
68175 1645	16,0	5/8	4,5	25,0	25	2	100	0,38	50
68175 1950	19,0	3/4	5,0	29,0	25	2	120	0,50	50
68175 2050	20,0		5,0	30,0	25	2	120	0,52	50
68175 2555	25,0	1	5,5	36,0	25	2	150	0,73	50



**KOMPRESORY
VZDUCHOTECHNIKA** s.r.o.
Vše pro stlačený vzduch na jednom místě

E: info@kompresory-vzduchotechnika.cz

E: objednavky@kompresory-vzduchotechnika.cz

T: +420 311 532 091, **M:** +420 773 489 530, **M:** +420 603 432 326