NEW!

MODY-CleanConnect-Spiral Hoses of Polyurethane

with straight ends for the food industry and pharmacy

- High-abrasion, pressure and wear resistance as well as extreme and constant recoil of the spirals
- Perfect elasticity, flexibility, can be driven over, crush-resistant, free of taste and smell
- Resistant to microbes and hydrolysis, oil, gas and chemical resistant, good cold flexibility
- Polyurethane food-safe according to FDA 21 CFR 177.2600 and 178.2010, EU regulation 10/2011 and the newest regulation 2015/174
- Approved according to the EU regulation 1935/2004
- Production process according to GMP EC 2023/2006
- For applications in the pneumatic sector as well as for liquids, gases and abrasive solids
- For applications in the food industry (e.g. food conveying, dry, watery, acidic and fatty foods), pharmaceutical industry (FDA, EU regulation)

Food-Safe

Clean Connect by LUDECKE

Materials

- Hose: polyurethane on polyether based
- Coupling, plug: stainless steel 1.4305

Max. Working Pressure	Temperature	Medium	Colours	Short End	Long End	
PN 12 bar	-40°C – +90°C	different	Transparent	100	500	1

Hose i.D./o.D.	Connection	Max. Working L. Hose Length		Block Length Outer Spiral∅		Weight	Type. Nr.
8/12	without	3000	4700	240	75	345	PUL 8123
8/12	without	6000	7600	400	75	555	PUL 8126
8/12	without	8000	9700	540	75	710	PUL 8128
8/12	ESE-coupling + plug	3000	4700	240	75	505	PUL 8123 ESE
8/12	ESE-coupling + plug	6000	7600	400	75	715	PUL 8126 ESE
8/12	ESE-coupling + plug	8000	9700	540	75	870	PUL 8128 ESE





MODY-CleanConnect-Hose of Polyurethane, non-spiraled (minimum quantity 10m)

Hose i.D./o.D.	Weight g/m	Type. Nr.
8/12	80	PUL 812

